(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization** International Bureau



(43) International Publication Date 23 December 2004 (23.12.2004)

PCT

(10) International Publication Number WO 2004/110267 A2

(51) International Patent Classification7: 5/024

A61B 5/0205.

(21) International Application Number:

PCT/IL2004/000537

(22) International Filing Date: 17 June 2004 (17.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 156556

19 June 2003 (19.06.2003)

(71) Applicant and


(72) Inventor: SCHENKER, Eran [IL/IL]; 14 Israel Galili Street, 69377 Tel-Aviv (IL).

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished



by a set of ranges, each for a physiological parameter and each characterizing this life condition. The detector comprises a sensor unit adapted to sense at least two of the physiological parameters and to generate signals indicative of their values, a processor for receiving and processing the signals to arrive at these values, the processor further being adapted to disregard any value falling outside the range of the respective parameter and to produce a qualitative diagnosis based on values falling within its range. This diagnosis is indicative of whether the organism or part thereof suits the life condition. The detector further comprises indication means adapted to indicate the diagnosis. The detector may be assembled using a general-purpose programmable communication device, a standard medical sensor and a special cable adapter.

